

# User guide

## Antisporco

Water-based stain protection for porcelain tiles: it helps reduce dirt absorption, protects grout joints and makes cleaning easier.



### Technical data:

- Physical state: opalescent liquid
- Specific weight (g / cm<sup>3</sup>): 1
- pH: 6-7
- Flashpoint (ASTM): not flammable
- Solubility in water: miscible
- Drying time: 15-30 min
- Consolidation time: 8-12 hours
- Odour: odourless

### Description:

Stain protection treatment for matte, polished and lapped porcelain tiles. Reduces the absorption of dirt and stains by creating an invisible, non-film-forming protective barrier that makes routine cleaning faster and easier without altering the appearance of the surface.

### Fields of application:

Invisible stain- and dirt-resistant protection specifically designed for porcelain tile floors and wall coverings. It significantly reduces dirt absorption, making routine cleaning faster and easier while helping maintain a more uniform surface over time.

### Characteristics:

ANTISPORCO is a stain protection treatment specifically developed for matte, polished and lapped porcelain tiles.

#### ANTISPORCO:

- creates an invisible, non-film-forming chemical stain barrier that does not alter the appearance or colour tone of the surface;
- is a water-based, odourless, non-hazardous and easy-to-use product;
- protects porcelain tiles and grout joints from everyday dirt and contamination;
- reduces surface absorption and makes routine cleaning easier and faster;
- helps reduce the use of cleaning products and the need for intensive washing;
- when applied before grouting, prevents grout residue from settling into the microporosity of the porcelain tile, making post-installation cleaning significantly easier;
- provides protection for approximately 6–12 months, depending on foot traffic and cleaning frequency, and can be easily reapplied over time.

### Instructions for use:

- Shake well before use.
- Apply ANTISPORCO only to perfectly clean and dry surfaces.
- Spray small amounts of product onto the surface and spread evenly with a soft cloth.
- The surface dries in approximately 10–15 minutes and can then be walked on.
- Maximum stain protection is achieved after approximately 12 hours. During this period, avoid washing the surface with water.
- Any excess product remaining after drying should be removed by wiping the surface with a cloth lightly dampened with ANTISPORCO.

It is recommended to apply ANTISPORCO® after an intensive stain-removal cleaning with POWER DET® or after a periodic deep cleaning with GRES LINDO®, in order to thoroughly clean the porcelain tile surface before applying the protective treatment.

### Yield:

The coverage of ANTISPORCO® may vary depending on the surface finish, the microporosity of the porcelain tile and the application method (amount sprayed and uniformity of distribution). Under standard conditions, with a correct thin-coat application and even distribution using a soft cloth: 750 ml = 30–40 m<sup>2</sup> or 1 L = 40–60 m<sup>2</sup>

#### Coverage on Polished or Very Dense Porcelain Tiles

Polished porcelain tiles are generally less absorbent and have a denser surface. As a result, less product is required. Approximate coverage: 750 ml = 40–60 m<sup>2</sup> (1 L = 55–80 m<sup>2</sup>)

#### Coverage on Matte or Satin Porcelain Tiles

Matte porcelain tiles have greater microporosity than polished surfaces and tend to absorb both dirt and protective treatments more easily. Approximate coverage: 750 ml = 30–40 m<sup>2</sup> (1 L = 40–60 m<sup>2</sup>)

#### Coverage on Structured / Slip-Resistant Porcelain Tiles (e.g. R10–R11)

Structured or slip-resistant surfaces have a rougher texture and a larger surface area. As a result,

the product spreads over more micro-relief points and coverage decreases. Approximate coverage: 750 ml = 20–30 m<sup>2</sup> (1 L = 25–45 m<sup>2</sup>)

#### Precautions:

- None.

#### Warnings:

**Hazard statements:** safety data sheet available on request.  
Rev4-Ver150322

#### Notes:

Our recommendations are based on current research knowledge and are intended to give the best information to the buyer-user. However, these indications require preliminary examinations and tests to the fields of use, to the types of materials present and to the various conditions of application. The user decides independently on suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev4-Ver150322

#### Storage:

Keep the product tightly closed at temperatures between 0 ° C and + 30 ° C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

#### Packaging:

- 750 ml PE spray bottle – boxes of 6 units
- 5 L PE canister – boxes of 4 units

