

# User guide

## Sani-Kal Forte

Professional bathroom limescale remover for stubborn deposits.  
Indicated for intensive cleaning on taps, ceramics, shower glass and



### Technical data:

- Physical state: colourless liquid
- Specific gravity (g/cm<sup>3</sup>): 1,03
- pH (20°C) of the pure product: 2
- Flame point (ASTM): non-flammable
- Solubility in water: soluble in water.
- Fragrance: fresh sanitary scent

### Description:

Professional limescale cleaner with controlled descaling action for intensive cleaning of bathroom surfaces affected by stubborn build-up. It removes limescale deposits, soap residues, urine stains, and rust marks, leaving surfaces clean, shiny, and bright.

### Fields of application:

SANI-KAL FORTE is recommended for removing limescale deposits from all acid-resistant surfaces, especially:

- sanitary ware
- taps and fittings
- showers and shower enclosures
- ceramic wall and floor tiles
- glass surfaces
- stainless steel surfaces

### Characteristics:

SANI-KAL FORTE is a controlled-action descaling cleaner designed for intensive bathroom cleaning.

The product:

- removes heavy limescale deposits, urine stains, rust marks, and soap residues
- does not release fumes and contains no hydrochloric acid
- leaves surfaces clean, glossy, and bright
- It is also easy to apply on shower walls and other vertical surfaces.

### Instructions for use:

The product is ready to use and must be applied to cold surfaces.

During application, wearing protective gloves is recommended.

- Apply the product directly onto the surface to be treated, spreading it evenly
- Leave it to work for a few minutes to allow the descaling action
- Rub with a soft cloth; in the presence of heavy limescale deposits, use a white pad
- Rinse thoroughly with water

In the case of particularly stubborn encrustations, increase the contact time before rinsing.

### Yield:

The coverage of SANI-KAL FORTE varies depending on the level of encrustation, the type of surface, and the contact time required to achieve effective descaling.

- In the presence of light limescale or surface deposits, such as regularly maintained areas or non-layered build-up, one 750 ml bottle can treat approximately 25–30 m<sup>2</sup>. In these conditions, the product ensures even coverage with moderate consumption.
- When dealing with medium limescale or more consistent mineral deposits, which require longer contact time and more vigorous rubbing, coverage may gradually decrease to around 20–25 m<sup>2</sup>. The actual yield depends on the amount of product applied and the method of application.
- In cases of stubborn limescale or resistant encrustations, where a higher dosage and extended action are necessary to ensure complete removal, coverage may decrease further. However, it remains indicative and subject to variation based on operating conditions.

The stated quantities should be considered approximate values. Actual consumption depends on the type of surface treated, the level of build-up, and the operator's application technique.

### Precautions:

Do not use SANI-KAL FORTE on:

- slate
- polished marble
- polished travertine
- polished cement-based agglomerates
- materials that are not resistant to acidic substances

## Warnings:

### WARNINGS: DANGER

**Hazard statements:** Causes severe skin burns and eye damage.

**Precautionary statements:** Do not breathe dust/fume/gas/mist/vapours/spray. - Wear protective gloves / eye protection / face protection. - Immediately call a POISON CENTER/doctor/... - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. - IF SWALLOWED: rinse mouth. Do NOT induce vomiting. - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

**Contains:** Phosphoric acid 75 %

Ingredients compliant with Regulation (EC) No. 648/2004:

Phosphors less than 5 %, non ionic surfactants less than 5 %. Perfume.

UFI: 3G20-M0HK-X00X-U1QJ

Rev8-Ver090222

## Notes:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev8-Ver090222

## Storage:

Keep the product tightly closed at temperatures between 0 °C and +30 °C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

## Packaging:

- 750 ml PE spray bottle – boxes of 6 units
- 5 L PE jerrycan – boxes of 4 units

