


User guide

Lignolife Opaco

Restore worn matte varnished parquet with a natural matte finish while improving protection against dirt, water and everyday wear.



Technical data:

- Physical state: white liquid
- Specific weight (g / cm³): 1.025
- pH: 8
- Flashpoint (ASTM): not flammable
- Solubility in water: miscible in water
- Drying time: 2 - 3 hours
- Consolidation time: 24 hours
- Odour: characteristic

Description:

Water-based resin-wax finish for renewing matte varnished parquet and matte varnished wood surfaces. Restores colour, uniformity and a natural matte finish while improving the coating's resistance to foot traffic, dirt, water and routine cleaning.

Fields of application:

LIGNOLIFE® OPACO is recommended for:

- matte varnished parquet;
- matte varnished wood wall coverings;
- matte varnished wooden furniture;
- matte varnished interior doors and window frames.

Characteristics:

LIGNOLIFE® OPACO is a water-based resin-wax finish containing carnauba wax, specifically developed for renewing matte varnished parquet and matte varnished wood surfaces. LIGNOLIFE® OPACO:

- is easy to apply and odourless;
- is designed for renewing matte varnished parquet and wood surfaces that have lost their original colour and uniform appearance;
- restores colour and provides a natural matte finish;
- forms a new protective film that improves the coating's resistance to foot traffic, dirt, water and cleaning agents;
- is self-levelling and provides a smooth, even finish;
- is easy to maintain over time with regular cleaning using PULIBRILL® and the application of BEAUTY FLOOR OPACO every 6–12 months.

LIGNOLIFE® OPACO does not replace re-varnishing where the original coating has been completely worn away. Where bare wood is exposed, for example in greyed areas or where water is directly absorbed by the wood, the varnish must first be restored.

Instructions for use:

Before applying LIGNOLIFE® OPACO, thoroughly clean the surface with PULIBRILL® and a WHITE PAD to remove dirt and residues that could affect the product's adhesion.

- Shake the product thoroughly before use.
- Apply 2 coats of LIGNOLIFE® OPACO using a wax applicator fleece, a microfibre cloth or a sponge.
- Spread the product in a thin, even coat, ensuring uniform coverage and avoiding excess product.
- Apply the second coat as soon as the first one is completely dry.
- Allow the treatment to dry. Under normal conditions and in well-ventilated areas, drying usually takes 2–3 hours.

Do not apply the product to surfaces colder than 7°C or to hot surfaces, such as heated floors in operation or surfaces exposed to direct sunlight. Do not apply with a brush or roller and do not use the product outdoors.

Yield:

The coverage of LIGNOLIFE® OPACO may vary depending on:

- the absorbency of the surface;
- the application method;
- the thickness of the applied coat;
- the number of coats applied.

Approximate coverage

1 L = 30–40 m² per coat Actual coverage may vary depending on the absorbency of the surface,

the amount of product applied and the application method.

Precautions:

- avoid application by brush or roller. Do not use outdoors;
- avoid applying LIGNOLIFE on surfaces that are too cold ($<7^{\circ}\text{C}$);
- avoid using strong alkaline and acid detergents (eg ammonia, sodium hypochlorite, various acids) and solvents (eg ethyl alcohol) when cleaning surfaces treated with LIGNOLIFE OPACO;
- avoid applying the product on surfaces that are too hot (eg radiant floors or floors exposed directly to the sun's rays).

Warnings:

Hazard statements: Safety data sheet available on request.

Contains: Rosin acids, fumarated, esters with pentaerythritol. May produce an allergic reaction.

VOC (Directive 2004/42/EC): One-pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition: 19,00. - Limit value: 140,00 Rev1-Ver300322

Notes:

Our recommendations are based on current research knowledge and are intended to give the best information to the buyer-user. However, these indications require preliminary examinations and tests to the fields of use, to the types of materials present and to the various conditions of application. The user decides independently on suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev1-Ver300322

Storage:

Keep the product tightly closed at temperatures between 0°C and $+30^{\circ}\text{C}$ and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

Packaging:

- 1 L PE bottle – boxes of 6
- 5 L PE canister – boxes of 4

