

User guide

Smacchia Infissi

Wood window stain remover for sun-damaged frames. Removes greying, mold and oxidation, restoring the natural color of wood surfaces.

Technical data:

- Physical state: clear, colorless liquid.
- Specific gravity (20°C): 1.035.
- pH (20°C): 1–2.
- Flash point (ASTM): non-flammable.
- Water solubility: soluble in water.
- Odor: characteristic.

Description:

Restorative stain remover specifically designed for wooden windows and frames exposed to sun and weather conditions. Effectively removes greying, oxidation, stains, and surface marks. Restores the natural appearance of wood and prepares it for protective treatments.

Fields of application:

Recommended for stain removal cleaning and restoration of:

- wooden windows and frames exposed to weather conditions
- interior and exterior wooden doors and entrance doors
- wood surfaces greyed, faded, or oxidized by sun exposure
- wood affected by mold, algae, and surface darkening
- surfaces treated with painted or oil-based finishes

Characteristics:

SMACCHIA INFISSI is a restorative stain remover specifically designed for wooden windows and frames exposed to sunlight and degraded by weather conditions. In particular:

- removes grey patina caused by ageing, yellowing, fading, and surface oxidation of the wood;
- eliminates algae, mold, and dark stains caused by moisture and weather exposure;
- restores the natural appearance of wood without the need for full sanding;
- can be used on wooden windows, frames, doors, and shutters with painted or oil-based finishes;
- prepares the surface for subsequent protective treatments such as OLIO RAVVIVANTE.

Instructions for use:

Ready-to-use product. Apply on surfaces that are not too hot. During application, the use of protective gloves is recommended.

- Shake well before use.
- Apply the product evenly to the surface to be treated.
- Leave to act, keeping the surface wet for about 20 minutes, or longer depending on the level of greying to be removed.
- Rub with BLUE BUFFER PAD or a rough sponge until stains are removed.
- Clean the surface with PULI INFISSI to neutralize the product action.
- Rinse thoroughly with clean water.
- Once dry, lightly finish with 100-grit sandpaper or ABRASIVE WOOD BUFFER PAD.

In case of persistent greying or stains, increase the contact time and repeat the application if necessary.

Yield:

The product coverage depends on the level of wood deterioration, the absorption of the material, and the contact time. With a 750 ml bottle, the estimated coverage is as follows:

- Treatment on lightly soiled or regularly maintained window frames In the presence of slightly greyed wood or superficial oxidation, 750 ml allows treatment of approximately 10–12 m² of surface.
- Treatment on moderately soiled window frames In case of widespread greying and weather-related stains, 750 ml allows treatment of approximately 8–10 m².
- Treatment on heavily deteriorated or greyed wood In case of severe degradation, darkening, or mold, a higher amount of product and longer contact time may be required. Under these conditions, coverage may decrease to approximately 6–8 m².

The values indicated are approximate estimates and may vary depending on the condition of the surface, the size of the frames, and the application method.

Precautions:

Before use:

- always carry out a preliminary test on a small area;
- do not apply on surfaces that are too hot or exposed to direct sunlight;
- protect surrounding vegetation from contact with the product;

- use appropriate protective equipment to avoid contact with skin and eyes.

Warnings:

WARNINGS: DANGER

Hazard statement: Causes serious eye damage.

Precautionary statements: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. – Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/... – Immediately call a POISON CENTER/doctor/ ...

Contains: Oxalic acid dihydrate

Ingredients compliant with Regulation (EC) No. 648/2004:

Non-ionic surfactants less than 5%

UFI: 7630-P01S-D00V-4SD2

Rev1-Ver14052025

Notes:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev1-Ver140525

Storage:

Store the product tightly closed at temperatures between 0°C and +30°C, avoiding prolonged exposure to direct sunlight. Under these conditions, the product has a shelf life of 2 years.

Packaging:

- 750 ml PE spray bottle – box of 6 units
- 750 ml PE spray bottle + BLUE BUFFER PAD + ABRASIVE WOOD BUFFER PAD

