

User guide

Biocare opaco

Water-based maintenance wax for matte oiled wood and parquet.
Renews surface protection, preserves the natural finish and makes
cleaning easier.

Technical data:

- Physical state: pink liquid
- Specific gravity (g/cm³): 1
- pH: 8
- Flame point (ASTM): non-flammable
- Solubility in water: miscible in water
- Drying time: 30 - 60 minutes
- Consolidation time: 24 hours
- Odour: characteristic

Description:

Water-based maintenance wax for oil-finished parquet and wood with a natural matte finish.
Renews surface protection, makes cleaning easier and helps preserve the original appearance of the finish over time.

Fields of application:

Recommended for the maintenance and protection of interior oil-finished wood surfaces with a natural matte finish, including:

- parquet and wood flooring;
- wall cladding;
- joinery;
- furniture;
- other oil-finished wood surfaces with a natural matte appearance.

Characteristics:

BIOCARE OPACO is a water-based maintenance wax specifically developed for interior oil-finished wood surfaces with a natural matte finish. In particular, it:

- renews the surface protection of matte oil finishes;
- helps preserve the appearance and protective properties of the finish over time;
- makes surfaces easier to clean and maintain;
- does not form glossy films or surface coatings;
- leaves a pleasant fresh scent.

Instructions for use:

Apply the product to clean, completely dry surfaces.

- Shake the container thoroughly before use.
- Apply a small amount of BIOCARE OPACO to a soft cloth and spread it evenly over the entire surface, creating a thin, uniform coat.
- Allow the product to dry completely and avoid walking on the surface while it is drying.
- Under normal conditions, BIOCARE OPACO dries in approximately 1–2 hours.

?Application frequency

- Every 4–6 months on heavily used surfaces exposed to frequent foot traffic, such as shops, public buildings, bars, restaurants, kitchens, entrances and bathrooms.
- Every 12 months on less frequently used surfaces, such as bedrooms, living rooms and sleeping areas.

Yield:

The coverage of BIOCARE OPACO may vary depending on the absorbency of the wood, the condition of the surface and the amount of product applied.

- On more absorbent surfaces or where a higher amount of product is required, 1 litre covers approximately 30 m².
- On less absorbent surfaces or those that are regularly maintained, 1 litre covers up to approximately 40 m².

The stated coverage values are approximate and may vary according to the application method and the characteristics of the wood.

Precautions:

- Do not use BIOCARE OPACO on varnished wood surfaces.
- Avoid using highly alcohol-based cleaners on surfaces treated with BIOCARE OPACO.

Warnings:

WARNING: NONE

Hazard statements: Safety data sheet available on request.

Rev3-Ver170322

Notes:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present, and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev3-Ver170322

Storage:

Keep the product tightly closed at temperatures between 0 °C and +30 °C and not exposed to sunlight for a long time. The stored product has a useful life of 2 years.

Packaging:

- 1 L PE bottle – boxes of 6 units
- 5 L PE jerrycan – boxes of 4 units

