

User guide

Biocare

Water-based maintenance wax for oiled wood floors and parquet that refreshes surface protection, makes cleaning easier and preserves the natural finish.

Technical data:

- Physical state: pink liquid
- Specific gravity (g/cm³): 1
- pH: 8
- Flash point (ASTM): non-flammable
- Solubility in water: total
- Drying time: 30 - 60 minutes
- Consolidation time: 24 hours

Description:

Water-based maintenance wax for parquet and interior oil-treated wood surfaces. Renews surface protection, makes cleaning easier and helps preserve the appearance of the finish over time. Does not form films or glossy layers.

Fields of application:

Suitable for the maintenance and protection of interior oil-treated wood surfaces, including:

- parquet and wooden floors;
- wall cladding and panelling;
- interior joinery;
- wooden furniture;
- other oil-treated wood surfaces.

Characteristics:

BIOCARE is a water-based maintenance wax specifically formulated for interior oil-treated wood surfaces. In particular, it:

- renews the surface protection of the oil treatment;
- helps preserve the appearance and protective properties of the finish over time;
- makes surfaces easier to clean and maintain;
- does not form films or glossy layers;
- leaves a pleasant fragrance in the room;
- its self-levelling formulation ensures even application and can be dry polished to enhance and maintain the surface's natural sheen.

Instructions for use:

Apply the product to clean and completely dry surfaces.

- Shake well before use.
- Apply BIOCARE in small amounts and spread it evenly with a soft cloth or a wax applicator pad.
- Allow the product to dry completely. Do not walk on the surface during the drying process.
- Once dry, polish the surface with a wool cloth, a polishing machine fitted with felt pads, a blue pad or a single-disc machine fitted with a blue pad to enhance the natural sheen and reduce signs of wear.
- BIOCARE normally dries within 1–2 hours.

Maintenance frequency

- Every 4–6 months on heavily used surfaces exposed to frequent foot traffic.
- Every 12 months on lightly used surfaces.

Yield:

Coverage depends on the absorbency of the wood, the type of finish and the amount of product applied. With 1 litre of BIOCARE, the approximate coverage is:

- 35–40 m² on low-absorbency surfaces or surfaces maintained regularly.
- 30–35 m² on more absorbent surfaces or surfaces requiring a greater amount of product.

The values shown are approximate and may vary depending on the characteristics of the wood and the application method.

Precautions:

- Do not use on varnished or lacquered wood surfaces.
- Avoid using highly alcoholic cleaners on surfaces treated with BIOCARE.

Warnings:

WARNING: NONE

Hazard statements: Safety data sheet available on request.

Rev3-Ver170322

Notes:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present, and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev3-Ver170322

Storage:

Keep the product tightly closed at temperatures between 0°C and +30°C and not exposed to sunlight for a long time. The product stored in this way has a useful life of 2 years.

Packaging:

- 1 L PE bottle – boxes of 6 units
- 5 L PE jerrycan – boxes of 4 units

